




Diaphragm type DP Gauge 600 DGC



- **AP Range : 0 to 25 up to 1250mm H₂O**
- **0 to 1 up to 50" H₂O**

Specifications

Accuracy	:	±3% of the FSD (Ascending)
Migraton	:	No migraton; Zero leakage from high to low port
Range	:	0-25 to 0-1250 mm of water
First marking on the scale	:	15% of the FSD
Sensing element	:	Diaphragm
Wettedparts	:	Diaphragm, Body material, SS 302 spring & ceramic magnet
Case material	:	Stainless steel (SS 304)
Dial size in inch /mm	:	112mm (4 9/16") Std.
Mountng	:	Flush (Std.) 2" pipe & surface mountng on request
Maximum working pressure	:	2.4 bar / 35 psi
Maximum process temperature	:	60°C / 130°F
Body material	:	Engineering Polymer
Seals	:	Buna-N, Viton ,EPDM diaphragm & 'O' rings
Window	:	Float glass (Std.), toughened glass, acrylic & safety glass
Connecton	:	1/8" NPT(F) Std.
Portng	:	In-line & back (user to select)
Over range protecti n	:	Up to the max. Working pressure from high
Protecton for gauge & switch	:	IP 65/ NEMA-4



Accessories supplied with the instruments

Option Switches (Adjustable in 40-80% of FSD)

Customer Logo	:	1 or 2 SPSTs with a DIN plug
Dual Scale	:	1 or 2 SPDTs with a DIN plug
Color Brand	:	

Switch can be added anytime in the field

Combination



Gauge



Switch



Gauge + Switch
(With DIN plug on top)



Mounting Baskets



Gauge
(Flush /Panel Mounting)



Gauge
(Surface Mounting)



2" Pipe Mounting



Authorised Dealer



NK Instruments Pvt. Ltd.

B-501/504, 5th floor, Raunak Arcade, Near THC Hospital, Gokhale Road, Naupada, Thane(W) 400602. Maharashtra INDIA
 E-Mail: sales@nkinstruments.com
 Skype: nitinkelkarskype

Telefax Nos.: 91-22-25301330 / 31 / 32
 Web: http://www.nkinstruments.com
 Gtalk: nkinstruments2006

